



Forced Ejection Scrapers

Pull Type Graders



Box Scrapers

Earth Packers



The Earth Movers and Shapers






Forced Ejection Scrapers

"The Strobel Forced Ejection Scraper is extremely heavy duty - yet very easy to operate. This is the machine I've been looking for. It has exceeded my expectations in every way."

— Jack, Poseyville, IN



FE 1200 Dolly Hitch

Guide Rollers: Adjustable 3" greasable concave rollers

Cutting Blades: Low profile design and 3-piece hi-strength blades

Strobel Strong Sides: Corrugated smooth walls provide slick surface on the inside and outside for cleaner and more efficient loading/unloading

Tires: Heavy duty industrial tires and rims with ten bolt hubs

Pivot Points: All pivot points are anti-rotational and greasable

INNOVATIVE

**Available in
8.5 & 12 Yard**

**FE 850 – 8 Foot Cut
FE 1200 – 10 Foot Cut**

Tongue or Dolly Hitch



Corrugated Sidewall,
Adjustable & Greasable Rollers




Adjustable Cleanout
Blade



Anti-Rotational Pins
& Cross Tube Cylinders

Pull Type Graders

"I use my Strobel Pro Grader all year; it's tough and more versatile than a motor grader – plus one less engine in the fleet. Many of my employees operate it and I've rented it to area farmers; everyone finds it to be very user-friendly."



– Ryan Roberts, Owner
Mid-Nebraska Land Developers
Aurora, NE

- Proportional Hydraulic Controls:** 12 volt push button controller functions with single tractor lever for superior machine control; requires only one hydraulic bank
- Five Function Blade Operation:** Tilt, angle, lift, roll and side shift provide ultimate versatility
- Staggered Walking Tandem:** Maximizing stability with 8-ply single ribbed tires
- Factory Filled & Sealed Weight Box:** 9,300 lbs of weight provides stable operation
- Cylinders:** Exclusive cross tube design with greasable anti-rotational pins
- Cutting Blades:** Replaceable 8" carbon steel – curved and beveled
- End Plates:** Fold-away, storable doors easily convert to a box scraper
- Swing Tongue:** 5 foot left or right movement gives maximum reach
- Swivel Hitch:** 360 degree, heavy-duty clevis or spade/hammer-strap options

VERSATILE

OPTIONS: Single Spade Hitch, Wireless Remote Controls, LED Light Package, 12' & 14' Blades



Offset Walking Tandem
Wheels & Enclosed Weight Box



Hydraulic, Adjustable
Blade Roll



Hydraulic Strobel
Side-Shift



Fold-Away, Storable Doors
Convert to Box Scraper



"I've had my Strobel Box Scraper for over ten years now... the only thing I've done is replace the blades."

– Neil, Scottsbluff, NE

EXTREME DUTY (XD)

12 Foot • 14 Foot

GENERAL PURPOSE (GP)

8 Foot • 10 Foot • 12 Foot



MEDIUM DUTY (MD)

10 Foot • 12 Foot • 14 Foot



HEAVY DUTY (HD)

10 Foot • 12 Foot • 14 Foot • 16 Foot



Side Supports: Tapered and beveled for extra strength and durability

Curved Cutting Blades: Unique design cuts quickly and accurately

Welded Tongue: Tongue is welded to the back of the scraper rather than bolted or welded to the front support

Pivot Points: All pivot points are anti-rotational and greasable

MD and HD Models Feature:

- Swivel tongue and various hitch and tongue options
- Optimal back and dump height
- Leading front and side replaceable cutting blades
- Machined bushings and anti-rotational pins provide a tighter tolerance which results in a longer life

OPTIONS: Tilt Axle, Dual Wheels, Spade Hitch



LIGHT DUTY (LD)

6 Foot • 8 Foot • 10 Foot



Heavy Duty Sidewall



Optional Dual Wheels



360 Swivel Clevis Hitch

RELIABLE

Earth Packers

“This machine is heavy duty — it’s really built to last. And, it makes my life simpler ...the hydraulic lift wheels let me move it from job to job easily and quickly.”

– Brad, Red Deer, Alberta, Canada



Extra Strength Construction: 1/2" Industrial strength sidewalls and high strength removable cross shaft

High Capacity for Extra Weight: Holds 1,175 gallons of liquid

Working Dimensions: Single drum is 5' high & 8' wide; double drum is 5' high & 9' wide

Double Roller Bearings: Heavy duty 2 15/16" Timken® Type E bearings

One Piece Shaft: Industrial duty shaft extends through the entire drum

Chevron Tooth Pattern: Cleans on every revolution for smooth operation

Hardened Stoodite® Teeth: 30% more teeth equals superior compaction

Dual Mounted Cross Tube Welded Lift Cylinders: Dual design spreads the weight load

OPTIONS: Swivel Hitch, Rear Hitch, Tongue Options, Smooth Drum



Double Drum Model



Hydraulic Lock for Transport



Clean Out Blades

DURABLE

Specifications

Box Scrapers

| | LD 6 | LD 8 | LD 10 | GP 8 | GP 10 | GP 12 | MD 10 | MD 12 | MD 14 |
|-----------------------------|--------------|--------------|--------------|---------------|---------------|---------------|--------------------|--------------------|--------------------|
| Width | 6' | 8' | 10' | 8' | 10' | 12' | 10' | 12' | 14' |
| Capacity | 1.5 cu yd | 2 cu yd | 2.25 cu yd | 2.25 cu yd | 2.75 cu yd | 3.3 cu yd | 3.5 cu yd | 4 cu yd | 4.5 cu yd |
| HP Required | 25 - 75 | 25 - 100 | 25 - 100 | 80 - 125 | 100 - 150 | 125 - 175 | 125 - 175 | 150 - 200 | 175 - 275 |
| Weight | 735 lbs | 980 lbs | 1225 lbs | 2050 lbs | 2350 lbs | 2650 lbs | 3000 lbs | 3500 lbs | 3900 lbs |
| Side Plate Thickness | 1/4" | 1/4" | 1/4" | 3/8" | 3/8" | 3/8" | 3/8", 3/4" leading | 3/8", 3/4" leading | 3/8", 3/4" leading |
| Back Height | 24" | 24" | 24" | 30" | 30" | 30" | 36" | 36" | 36" |
| Dump Height | 15" | 15" | 15" | 20" | 20" | 20" | 30" | 30" | 30" |
| Tire Size | 75/R15 ST205 | 75/R15 ST205 | 75/R15 ST205 | 11Lx15 (8ply) | 11Lx15 (8ply) | 11Lx15 (8ply) | 1110x16 (10ply) | 1110x16 (10ply) | 1110x16 (10ply) |

Box Scrapers

| | HD 10 | HD 12 | HD 14 | HD 16 | XD 12 | XD 14 |
|-----------------------------|-----------------|-----------------|-----------------|-----------------|------------|-------------|
| Width | 10' | 12' | 14' | 16' | 12' | 14' |
| Capacity | 5.5 cu yd | 6.5 cu yd | 7.75 cu yd | 8.5 cu yd | 11 cu yd | 12.75 cu yd |
| HP Required | 150 - 225 | 175 - 250 | 200 - 275 | 225 - 300 | 250 + | 300 + |
| Weight | 4900 lbs | 5300 lbs | 5900 lbs | 6500 lbs | 10200 lbs | 11900 lbs |
| Side Plate Thickness | 5/8" | 5/8" | 5/8" | 5/8" | 3/4" | 3/4" |
| Back Height | 45" | 45" | 45" | 45" | 72" | 72" |
| Dump Height | 36" | 36" | 36" | 36" | 36" | 36" |
| Tire Size | 16.5-16 (10ply) | 16.5-16 (10ply) | 16.5-16 (10ply) | 16.5-16 (10ply) | 395/85 R20 | 395/85 R20 |

Pull Type Pro Graders

| | PG 12 | PG 14 |
|---------------------------|--------------------------------|--------------------------------|
| Blade | (2) 5/8" x 8" x 6' | (2) 5/8" x 8" x 7' |
| Transport Width | 8' 6" | 9' 10" |
| Transport Length | 14' 9.5" | 15' 6" |
| Approximate Weight | 9200 | 9300 |
| Spindles | (4) 2-1/4" OD x 17" / 4,500 lb | (4) 2-1/4" OD x 17" / 4,500 lb |
| Rim | 8 bolt | 8 bolt |
| Tire Size | 11Lx15 (8 ply) Tru-Trac | 11Lx15 (8 ply) Tru-Trac |
| Blade Swing | 45 deg | 45 deg |
| Tilt | 15 deg | 15 deg |
| Pitch | 55 deg | 55 deg |
| Lift Cylinder | 3.5" x 24" | 3.5" x 24" |
| Side Shift | 60" | 60" |
| Hyd. Remotes Req. | 1 | 1 |
| HP Required | 150 - 200 | 200 - 250 |

Earth Packers

| | (SD) Single Drum | (DD) Double Drum |
|-----------------------------------|------------------|------------------|
| Number of Drums | 1 | 2 |
| Overall Length | 18' 7" | 20' 1" |
| Overall Width | 9' 1" | 10' 2" |
| Length of Each Drum | 8' | 4' |
| Diameter of Each Drum | 5' | 5' |
| Max. Ground Clearance | 12" | 12" |
| Number of Teeth | 225 | 240 |
| Empty Weight | 9,700 lbs | 10,020 lbs |
| Pressure Sq In (Empty) | 240 lbs | 248 lbs |
| Weight (Filled with Water) | 19,511 lbs | 19,831 lbs |
| Total Capacity | 1,175 gal | 1,176 gal |

Forced Ejection Scrapers

| | FE 850 Tonque | FE 850 Dolly | FE 1200 Tonque | FE 1200 Dolly |
|--------------------------------|---------------|----------------|--------------------|--------------------|
| Cut Width | 8' | 8' | 10' | 10' |
| Capacity - Heaped | 8.5 cy | 8.5 cy | 12 cy | 12 cy |
| Capacity - Struck | 7.5 cy | 7.5 cy | 9.8 cy | 9.8 cy |
| HP Required | 100 - 200 | 100 - 200 | 185 - 300 | 185 - 300 |
| Max. Cut Depth | 9" | 7" | 9" | 7" |
| Max. Dump Height | 24" | 18" | 24" | 18" |
| Ground Clearance | 20" | 20" | 20" | 20" |
| Weight | 11,950 lbs | 13,000 lbs | 12,950 lbs | 14,000 lbs |
| Overall Height | 5' | 5' | 5' | 5' |
| Overall Length | 21' | 21' | 21' | 23' |
| Overall Width | 9' 2" | 9' 2" | 11' 2" | 11' 2" |
| Pull Point to Rear Axle | 18' 8" | 23' | 18' 8" | 23' |
| Tire Size - Front | NA | 40 x 14.5 x 19 | NA | 40 x 15 x 19.5 |
| Tire Size - Rear | 395-85R20 | 395-85R20 | R16 x 20 | R16 x 20 |
| Rim | 8 bolt | 8 bolt | 10 bolt | 10 bolt |
| Spindles | 3" / 8,000 lb | 3" / 8,000 lb | 3.125" / 12,000 lb | 3.125" / 12,000 lb |
| Wheel Base | NA | 16' | NA | 16' |
| Cylinder - Front Gate | 3" x 14" | 3" x 14" | 3" x 14" | 3" x 14" |
| Cylinder - Eject | 4" x 48" | 4" x 48" | 5" x 48" | 5" x 48" |



Since 1946, the Strobel name has been synonymous with high quality, durable products that meet the needs of customers across the country and around the world. Throughout the last seven decades, "innovation" has been forefront - beginning with Leonard Strobel's blacksmith shop in the early days to the next generation of products for farmers, contractors, feedlots and ranches.



In 2008, Steve and Belinda launched Strobel Manufacturing (formerly Strobel Industries). Their commitment to family and faith permeates every part of the company - serving and caring for the employees, the customer and the broader community in which they live.

Today, the entire Strobel team remains committed not just to innovation, but to the strong tradition of integrity, character and quality craftsmanship. Every piece of machinery carries the Strobel Strong Warranty - covering parts, material and workmanship. This industry-leading warranty gives the customer peace of mind and hassle-free protection.



At Work...Strobel Strong

16 Models Available - Lowest Center of Gravity



2 Box Lo-Profile Seed Tender



BT 300 Bulk Seed Tender



4 Box Lo-Profile Seed Tender



BT 200 Bulk Seed Tender



4 Box Seed Tender Skid



2 Box Standard Seed Tender



BT 200 Bulk Seed Tender Skid

